

Lick

Product Information



NAME

Lick Interior Eggshell Emulsion

DESCRIPTION

A high quality acrylic eggshell paint suitable for use on walls, ceilings and woodwork.

Perfect for interior applications including kitchens, bathrooms and high traffic zones.

A mid-sheen eggshell finish with a noticeable soft gloss.

PREPARATION

Surfaces must be sound, clean and free from wax, grease, oil, dust and loose particles. On existing painted surfaces remove all loose and flaking paint and thoroughly rub down with abrasive paper. Prime any bare surfaces with appropriate primer. New plaster and cement should be allowed to dry thoroughly before application. Previously unpainted porous surfaces should be treated with a first coat thinned up to 30% with clean water. Previously unpainted woodwork should be primed with a thinned coat as above. Any ferrous metal surfaces should be primed with an all-metals primer. Any areas subject to staining should be treated with a stain block.

APPLICATION

- Stir thoroughly and check colour before use.
- Apply by brush, roller or spray, applying after priming coat (if necessary) with two coats.
- If using multiple batches – ensure they are intermixed before use.
- Ensure air and surface temperatures are above 8 degrees centigrade.

SPRAY APPLICATION

- Airless: Tip Size 15 – 17thou 50-degree angle with a pressure of around 2500psi
- HVLP (High Volume Low Pressure) or conventional spray – 1.8mm needle nozzle set up

PROPERTIES

GLOSS	20%
TOOLS	Brush, roller, spray
CLEAN	Warm soapy water
DRY TIME	At 18-degrees centigrade and 65% humidity: <ul style="list-style-type: none">● Touch dry in 1 hour● Recoatable after 4 hours
COVERAGE	11-13sq. metre per litre depending on porosity of substrate surface texture and application method.
SURFACES	Indoor use across: <ul style="list-style-type: none">● Wood – doors, furniture, trim/skirting and cornicing● Previously painted walls● Wallpapered walls● Ceilings● Metal● Brick and mortar

SIZES	2.5L
VOC	< 30g/L
STORAGE	Protect from frost. Keep out of reach from children. After first use, re-seal with plastic bung. Do not screw metal lid back on once the rim is exposed to paint.
CARE	New paintwork should not be exposed to steam or condensation for 72 hours. Protect the coating against abrasive contact for 7 days. After 7 days the finish can be cleaned with a mild detergent solution and a soft cloth.
DISPOSAL	Protect our environment. Waste packaging should be recycled. Empty containers can be recycled. Leftover product should be disposed of in compliance with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilt material, runoff and contact with soil, waterways, drains or sewers.
SAFETY	Please contact us for full safety data via hello@lickhome.com