



## Pyure Slimline<sup>™</sup> Hydroxyl Generator Air & Surface Protection

**Product Specifications** 





## **Slimline<sup>™</sup> Purifier**

The Slimline<sup>™</sup> hydroxyl generating purifier is designed for smaller spaces where a portable or wall-mounted unit is sought. It is ideal for offices and schools, senior living, conference and waiting rooms, and other commercial applications that need to sanitize and deodorize indoor spaces.

The table below summarizes the minimum treatment area in absence of ventilation, and the treatment area range under typical conditions: 3 air changes per hour, 90% recirculated air and 2.7 meters ceilings. These guidelines should be adhered to for optimal performance and safety.

Operating Guideline		
Minimum Area (if there is no air circulation)		2m <sup>2</sup>
Treatment Range		0 - 84m²
Specifications		
Dimensions (LxWxD)	457mm x 133mm x 635mm	
Weight	7.9kg	
Voltage	230V @ 50Hz	
Power	170 Watts (Max)	
Number of Optics	1	
Noise Level	52.8dBA - 69.9dBA	
Airflow*	180 CFM *Airflows were measured with new/clean units	
Filter	Washable filter 127mm x 317.5mm x 6.4mm	
Shipping Dimensions	533mm x 229mm x 737mm	
Shipping Weight	9.8kg	
Certification	UL 507, CSA C22.2 #113, CE, RoHS, REACH	
Warranty	2 years covering defects in workmanship or materials, but excluding spare parts and consumables	



Copyright 2022, The Pyure Company. Slimline<sup>™</sup> is a trademark of The Pyure Company, Boynton Beach, FL 33426 USA Distributed by:



info@magab.se www.magab.se