



Figure

CRANEFRIGOR™ CVD

The CRANEFRIGOR™ CVD liquefier was developed for reliable and long-term operation under extreme ambient conditions as in harbours. Thanks to its robust structure, a reliable operation is ensured even with heavy shocks.

The CRANEFRIGOR™ series of crane air conditioning units ensure a reliable and efficient production process.

The condensing unit CRANEFRIGOR™ CVD is only approved for evaporating temperatures $> -10^{\circ}\text{C}$ and is therefore not covered by Ecodesign Directive 2009/125/EC.

General description

Scope of delivery	Your benefits!
<p>Compressor (made by Copeland)</p> <ul style="list-style-type: none"> • Hermetically sealed construction • Suction-gas-cooled motor • Self-regulating oil sump heater 	<ul style="list-style-type: none"> • Low maintenance • No risk of overheating • Ensures lubrication during the start • Very good availability of spare parts worldwide
<p>Liquefier</p> <ul style="list-style-type: none"> • Zinc-plated steel housing with epoxy-coated aluminium blades 	<ul style="list-style-type: none"> • Excellent heat transfer • Shorter maintenance intervals due to special adapted spacing between blades even with extreme dust load • Shorter maintenance intervals due to smooth surface
<p>Liquefier fan</p> <ul style="list-style-type: none"> • Speed-controlled EC axial fan in industrial construction for high ambient temperatures 	<ul style="list-style-type: none"> • Powerful • Long runtimes • Energy-efficient
<p>Casing</p> <ul style="list-style-type: none"> • Robust, welded construction • Primed and powder-coated in RAL 3004 • Other colours or stainless steel version optional 	<ul style="list-style-type: none"> • Robust, welded construction • Primed and powder-coated in RAL 3004 • Other colours or stainless steel version optional
<p>Power cabinet</p> <ul style="list-style-type: none"> • Completely wired according to VDE • Powder-coated RAL 7035 • Optional stainless steel version 	<ul style="list-style-type: none"> • The CRANEFRIGOR™ is wired connection-ready on a terminal strip. • Colour scheme with high corrosion protection
<p>Quality assurance</p> <ul style="list-style-type: none"> • Leakage test • Presetting of the safety devices 	<ul style="list-style-type: none"> • Operational reliability • Easy commissioning on site

Options packages:

Material order no.	Scope of delivery	Your benefits!
807 576 807 577	Options packages “Corrosion protection” Corrosion protection package 1 Corrosion protection package 2	<ul style="list-style-type: none"> • Multiple-coated pipes • Housing / Plate parts made of high-quality stainless steel 1.4571 / AISI 316Ti • Multiple-coated pipes
807 578	Option package “Custom” Customer-specific version	<p>Special requirements of a company can be realised, such as:</p> <ul style="list-style-type: none"> • Custom voltages / Network configurations • Liquefier version (fully copper, blade spacing and thickness) • Conductor identification • Special coatings • Protection class

Plant packages:

<i>Material order no.</i>	<i>Scope of delivery</i>	<i>Your benefits!</i>
807 566	Plant package “SMART Control” Superordinate controller FrigorTec Smart Control FSC	<ul style="list-style-type: none"> • Cyclic switching over for redundant systems • Digital display of pressures and temperatures • Optional regulation of the room pressure by filter/overpressure unit • Optional display of the relative room humidity
807 583	Plant packages “Internal unit (Evaporator)” Wall or ceiling version <ul style="list-style-type: none"> • Operation of several internal units on one liquefier possible • Epoxy-coated blades • Housing primed and powder-coated 	<ul style="list-style-type: none"> • Adjustment options as required for the project • Colour scheme with high corrosion protection
805 584	Optional housing in stainless steel version	<ul style="list-style-type: none"> • Increased corrosion protection
807 562	Plant package: “Overpressure / Fresh air” Filter/Overpressure unit FT15	<ul style="list-style-type: none"> • Filtered fresh air supply, adjustable air volume • Creation of overpressure in the room to be cooled; less dust comes in
807 579	Plant package “Condensation evaporator” Condensation evaporator KV1	<ul style="list-style-type: none"> • No damage due to dripping condensation • No additional power supply necessary • Overload protection
807 578	Plant package “Assembly material” <ul style="list-style-type: none"> • Refrigerant lines made of copper • Solenoid valves, expansion valves, filter drier, sight glasses • Thermostats • Insulation for suction line • Refrigerant • Plumb-line 	<ul style="list-style-type: none"> • Adjustments and planning as required for the project must be made in advance.

Technical specifications CVD:

Performance data

Cooling performance is included customised in the offer

Nominal cooling performance:

20 kW

- At 27 °C room temperature, 52 % rel. room air humidity
- 35 °C ambient temperature
- Refrigerant R134a / R513A

Cooling mode

- Depending on compressor size
- Depends on the option packages and version of heat exchanger

Temperature range

-17 °C to +54 °C

- More extreme temperatures upon request

Sizes and weight

Weight

approx. 290 kg

Dimensions

type, see dimension sheet

Operating voltage

3 ph / 400 V / 50 Hz

Further operating voltages upon request

3 ph / 460 V / 60 Hz

Protection category

IP54

Network type

TN-S

Refrigerant

R134a / R513A / R410A

GWP (global warming potential)

1430 / 631 / 2088

Filling quantity / CO2 equivalent

depends on the unit version

The performance description is a quality in the sense of sections 434 and/or 633 BGB (German Civil Code).

Subject to technical change.

According to (EN) 378-3 „Refrigeration units and Heat pumps – safety and environment regulations – Location and protection for persons” detectors needs to installed if concentration exceeds the practical limits (ATEL/ODL- EN 378-1, Appendix C) in a working and staying area.

The table is showing the minimum space dependent from the used Freon, air-conditioner and options.

Detectors are required if the conditioned space is smaller as mentioned in the table below.

Local restrictions and regulations need to be considered first.

Refrigerant	Minimum conditioned space before detector is required
R134a	62,4 m ³
R513A	48,6 m ³
R410A	28,9 m ³

ATEL: Exposure limit value for acute toxicity

ODL: Limit value for oxygen deficiency