



Protect your home with the best waterproofing technology

**Hygrothane** Spray-Applied Waterproofing Membrane

Keeps Water Out Applied Year-Round Environmentally Conscious

### Trust Hygrothane for Long-Lasting Protection

Hygrothane is made from polyurea - a superior material and high tech approach to waterproofing. With Hygrothane for your foundation waterproofing, you can relax and be assured that water will not be an issue for your home.

**Durability:** Hygrothane forms a strong, seamless monolithic barrier against water intrusion, which means it can withstand a wide range of weather conditions as well as impact to its surface.

**Flexibility:** One of the key advantages of Hygrothane is its flexibility. It can adapt to the movements and settling of a home without cracking or weakening.

**Fast Application:** Unlike other materials that require multiple layers and extended curing times, Hygrothane can be applied in a single coat and cures rapidly.

## 켰

#### **All Season Application**

Waterproofing on your timetable with both summer and winter application

### $\bigcirc$

#### **Superior Performance**

The latest technology in waterproofing is now available to homeowners

**Cost-Effectiveness:** By investing in a high-quality waterproofing solution like polyurea, homeowners can potentially avoid costly repairs and replacements down the road.



#### **Monolithic Barrier**

No cracks or weak spots for water to get through. It's like a fortress around your home



#### **Durable & Lasting**

Excellent resistance to weather and impact to ensure long-lasting protection

**Environmentally Conscious:** 

Hygrothane contains zero VOCs and is bitumen free – making it the ideal choice for environmentally conscious homeowners.

## Hygrothane

### **Technical Data**

Attribute	Test	Results
Dry Film Thickness	ASTM D5147	1.27 mm (50 mils)
Elongation	CAN/CGSB 37-GP-56M	334% (MD) 347% (XD)
Water Vapour Transmission	ASTM E96	58 ng / (Pa·s·m²) @ 1.27mm or 50 mils
Water Absorption	CAN/CGSB 37.58-M86	0.43%
Low Temp Flexibility	CAN/CGSB 37.58-M86 ASTM C794	-40°C No Crack
Static/Dynamic Puncture	CAN/CGSB 37-GP-56M (-15°C)	Pass Rating 4
CCMC #	_	14144-R
Colour	-	Black

# HYGROTHANE

"After researching several waterproofing options, we chose Hygrothane and couldn't be more pleased. The installation was smooth, and the results have been fantastic. No more worries about water damage!"

David, Homeowner

All properties determined through testing by an accredited independent third party test facility.





**Elastochem Specialty Chemicals Inc.** 37 Easton Road Brantford, ON N3P 1J4 1–877–787–2436 www.elastochem.com | info@elastochem.com



Contact us for more information about residential waterproofing!