



DESCRIPTION

Standard throughout okoume plywood

USINGS

Exterior using for general purposes

This product is especially suitable for outdoor panels, walls, shutters, floors, doors.
For Marine, Train and Transport, Building industries

ADVANTAGES

- ✓ Naturally sustainable wood and water resistance
- ✓ Selected veneers
- ✓ Good weight/mechanical resistance rate
- ✓ Could be veneered or covered (sliced veneer, hpl, paint, varnish, aluminium, etc...)

COMPOSITION

Face 1 : Okoume rotary cut veneer 10/10° quality II

Face 2 : Okoume rotary cut veneer 10/10° quality III

Inner layers in selected peeled okoume veneers

WOOD SPECY

100% Okoume (500 kg/m³ +/-10%)

GLUING

EN 314-2 : Class 3 (EN 636-3) Exterior using

EN 717-2 : E1 very low formaldehyde emission

CTB-X and CE 2+ labels

SIZES

Regular sizes in mm : 2500x1220 - 3100x1530

Special sizes in mm : 2150x950 - 2500x1530 - 3100x1220

Any others sizes on request

Cross grain available on request

THICKNESSES

From 3 mm to 40 mm (every 1 mm)

Surface finishing sanded 2 faces

For any other thickness, please contact us

OPTIONS

Cut at size, CNC milling, grooving, varnishing, fireproof treatment

FSC certification on request



SAS ALLIN

RUE DE LA COUARDE - F-79270 LE VANNEAU

Tel : +33 5 49 35 00 02 – Fax : +33 5 49 35 02 64

E-mail : allin-sa@allin.fr – Site web : www.allin.fr